



# Scotch-Grip™

## Spray 77 Multi-Purpose Adhesive

---

### Product Data Sheet

---

Updated : August 1995  
Supersedes : November 1993

---

#### Product Description

Spray 77 Adhesive is a multi-purpose aerosol adhesive. It is fast tacking and has a long tack range when applied to both surfaces.

Spray 77 Adhesive 77 is a light coloured, non staining adhesive.

---

#### Physical Properties

Not for specification purposes

<b>Solvent</b>	Petroleum Distillate / Cyclohexane	
<b>Flash Point</b>	-46°C	
<b>Propellant</b>	Hydrocarbon	
<b>Contents</b>	349g (500ml)	
<b>Solids Content</b>	25% approximately	
<b>Spray Pattern</b>	Particle	
<b>Colour</b>	Clear/Pale Cream	
<b>Shelf Life</b>	12 months from date of receipt by customer when stored in the original carton at 21°C (70°F) & 50 % Relative Humidity	

---

#### Performance Characteristics

Not for specification purposes

<b>Service Temperature Range</b>	-30°C to 60°C	
<b>Water Resistance</b>	Very Good	
<b>Weathering Resistance</b>	Fair	
<b>Fuel and Oil Resistance</b>	Poor	
<b>UV Light Resistance</b>	Fair	

Date : August 1995  
 Spray 77 Multi-Purpose  
 Adhesive

<b>Additional Product Information</b>	<b>Coverage:</b> Approximately 12m <sup>2</sup> (140 square feet) per container, depending on porosity of substrate.	<b>Conformity to British Standards and Other Specifications:</b> Defence Standard 80-117	
<b>Storage Conditions</b>	Store at 16°C to 27°C for maximum storage life in a cool dry place. Storage temperature must not exceed 49°C.		
<b>Directions for Use</b>	<p>Ensure all surfaces to be bonded are clean, dry and free from dust, oil and grease before application of adhesive.</p> <p>Ensure that the nozzle points away from all persons and towards the surface to be sprayed. Turn the spray tip to select the desired spray width.</p> <p>Shake the can well before using, 5-10 seconds should be sufficient.</p> <p><b>For Strong Permanent Bonds:</b> Spray both surfaces to be bonded and allow a minimum of 30 seconds drying time before assembly.</p>	<p><b>For Temporary Bonds with Easy Removal:</b> To bond substrates for short periods and to permit easy removal, apply a light coat to one surface and allow to dry for about 1 minute. Most surfaces can then be removed when desired without adhesive transfer.</p> <p><b>NOTE:</b> When bonding expanded polystyrene foam, leave surface open for about 10 minutes to allow most of the solvent to escape before making a bond.</p> <p>To prevent spray nozzle from blocking, at the end of each day, turn the can upside down and press tip until spray is clear from adhesive.</p>	<p><b>Clean Up:</b> Spray nozzle or excess material may be cleaned with Scotch-Grip Solvent No. 1.</p> <p><b>NOTE:</b> Solvent No. 1 is highly flammable. When using solvents for clean up it is essential that proper safety precautions are observed.</p>
<b>Applications</b>	Spray 77 Adhesive is extensively used for bonding lightweight boards, foams, plastics, fabric, paper and insulating materials.	For bonding fabric backcloths in studios and window dressing, and bonding polystyrene foam in fabricating packaging units.	The adhesive is also widely used in the heating and ventilating industry.

Date : August 1995  
 Spray 77 Multi-Purpose  
 Adhesive

## Health & Safety Information

### Precautions:

Highly flammable. Vapours may ignite explosively. Vapour may be harmful. Keep away from heat. Keep away from sources of ignition including pilot lights and sparks - No Smoking. Avoid prolonged breathing of vapours/spray. Do not use in confined areas or areas with little or no air movement. Do not spray directly into eyes. Avoid prolonged or repeated contact with the skin. Keep out of reach of children.

### WARNING:

Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or incandescent material.

### First Aid:

#### Eye Contact:

Rinse immediately with plenty of water and seek medical advice.

#### Skin Contact:

Wash with soap and water.

For further information please contact our Toxicology Department at the Bracknell Head Office on (01344) 858000.

3M and Scotch-Grip are trademarks of the 3M Company.

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.



## Specialty Tapes & Adhesives

3M United Kingdom PLC  
 3M House,  
 28 Great Jackson Street,  
 Manchester,  
 M15 4PA

Customer Service :  
 Tel 0161 236 8500  
 Fax 0161 237 1105

3M Ireland  
 3M House, Adelphi Centre,  
 Upper Georges Street,  
 Dun Laoghaire, Co. Dublin,  
 Ireland

Customer Service :  
 Tel (01) 280 3555  
 Fax (01) 280 3509

© 3M United Kingdom PLC 1996