# **3M**

## 69 Glass Cloth Electrical Tape - OEM

### **Data Sheet**

#### **Product Description**

3M<sup>™</sup> 69 Glass Cloth Electrical Tape is a white glass cloth tape with a high-temperature thermosetting silicone adhesive. The thermosetting adhesive provides an increased bond once applied in areas of high ambient temperatures. 69 Tape is UL recognized for continuous use up to 200°C. It conforms to Military Specification No. MIL-I-19166C.

#### **Applications**

- Insulating electric and induction type furnace power supply leads
- Securing high temperature, non-PSA insulations (such as asbestos and glass) in high temperature areas

- Securing Scotch 77 Fire Retardant Electric Arc Proofing Tape
- Replacing 3M 27 Glass Cloth Electrical Tape in locations where a higher-temperature tape is needed
- Reinsulating and repairing coils on mining machines
- Reinforcing insulation in electrical installations where heavy loads cause high heat and breakdown of original insulation (e.g. motor control exciter feeds)
- Splicing silicone-covered glass wire where splices require more abrasion resistance and mechanical strength than can be provided by silicone tapes
- Insulating Class "H" dry-type transformer leads

#### **Typical Properties**

Property	Value*
Thickness <sup>1</sup>	7.0 mils (.177 mm)
Tensile Strength <sup>1</sup>	180 lbs./in (314 N/10mm)
Elongation at Break <sup>1</sup>	5%
Adhesion <sup>1</sup>	40 oz/in (4.4 N/10mm)
Electrical Strength <sup>1</sup>	3000V
Insulation Resistance <sup>1</sup>	4.8 x 10 <sup>7</sup> (megohms)
Electrolytic Corrosion Factor <sup>2</sup>	0.9
Functional for Life of Component	200°C

<sup>\*</sup>Not recommended for specification purposes. Product specifications will be provided upon request.

Test Methods: 1 ASTM D-1000

<sup>&</sup>lt;sup>2</sup> 3M Test Method

#### Important Notice

Technical information provided by 3M is based on experience and/or tests believed to be reliable, but their accuracy is not guaranteed and the results may not be relevant to every user's application. For this reason 3M does not accept responsibility or liability, direct or consequential, arising from reliance upon any information provided and the user should determine the suitability of the products for their intended use. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence. All questions of liability relating to 3M products are governed by the seller's terms of sale subject where applicable to the prevailing law

If any goods supplied or processed by or on behalf of 3M prove on inspection to be defective in material or workmanship, 3M will (at its option) replace the same or refund to the Buyer the price paid for the goods or services. Except as set our above, all warranties and conditions, whether express or implied, statutory or otherwise are excluded to the fullest extent permissible at law.

 $3\mbox{M}$  and Scotchcast are trademarks of the  $3\mbox{M}$  Company. Printed in the UK.

© 3M United Kingdom PLC, 1999

3M United Kingdom PLC Electrical Products Group Hudson Road Bedford MK41 0HR Tel: 01234 268868 Fax: 01234 229433

3M Ireland Electrical products Group 3M House, Adelphi Centre Dun Loaghaire, CO. Dublin, Ireland Tel: (01) 2803555

Fax: (01) 2803509



Jan. 2000