TECHNICAL DATA

Version 9

AT293 Premier Closure Plate Tape

General Description

A polythene extruded gloss cloth tape coated with Surefire® thermosetting adhesive.

- PRS10 approved
- Unique Surefire® thermosetting adhesive
- Very high tack
- Good high and low temperature resistance
- Strong
- Can be written on
- Excellent conformability to awkward shapes
- Good abrasion resistance
- Non-corrosive adhesive
- Water resistant finish
- Easy tear



Specification

*Meets British Gas specification PRS10 issue 2

Technical Details

Typical Values

0.28mm **Thickness**

Breaking Load 75N/cm

30% Elongation

Adhesion

Steel 4.5 N/cm

Self 3.2 N/cm

Aluminium 4.4 N/cm

Yes RoHS compliant

-50°C to +110°C Service Temperature

Application Temperature +5°C to +45°C

Storage Temperature +12°C to +25°C

NOTE

Except where indicated otherwise, the figures stated are average values and should not be regarded as MAXIMUM or MINIMUM values for specification purposes. The Company reserves the right to improve products and any change in specification will result in a reissue of the relevant 'Technical Data Sheet'. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modifications or otherwise. Please check that you have the latest issue of the 'Technical Data Sheet'. All slitting and length tolerances are to British Standards. Before use the customer is advised to consult the Health & Safety Data Sheet produced by the company for this product, which is available on request.

Tapes stored below the minimum recommended temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.





AFERA

Association des Fabricants Européens de Rubans Auto-Adhésifs.

Advance Tapes International Limited Westmoreland Avenue Thurmaston Leicester LE4 8PH England

Tel. +44 (0)116 251 0191 Fax. +44 (0)116 265 2046 contact@advancetapes.com



www.advancetapes.com

^{*}Standard charge for certificate: £25.00.