TECHNICAL DATA

Version 14

AT77 All Weather PVC Electrical Insulation Tape

General Description

A PVC film coated with an aggressive, rubber-resin adhesive...

- Flame retardant
- Self-extinguishing
- Good low temperature performance
- Flexible
- Conformable to awkward shapes
- · Good abrasion resistance
- · Good resistance to ageing
- UV resistant
- Non-corrosive adhesive

Specification

Certification* to the following standards may be available on request, BS EN 60454-3-1/Type 6 (Formerly BS 3924).

Technical Details

Typical Values

Thickness 0.19mm

Breaking Load 30 N/cm

Elongation 250%

Adhesion

Steel 2.6 N/cm

Self 2.5 N/cm

Moisture Vapour Permeability 40g/m²/24 hrs

Flame Retardancy Self-extinguishing

Breakdown Voltage 10 kV

RoHS Compliant Yes

Service Temperature -18°C to +80°C

Application Temperature -10°C to +80°C

Storage Temperature +12°C to +25°C

*Standard charge for certificate: £25.00.



NOTE

Except where indicated otherwise, the figures stated are average values and should not be regarded as MAXIMUM or MINIMUM values for specification purposes. The Company reserves the right to improve products and any change in specification will result in a re-issue of the relevant 'Technical Data Sheet'. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modifications or otherwise. Please check that you have the latest issue of the 'Technical Data Sheet'. All slitting and length tolerances are to British Standards. Before use the customer is advised to consult the Health & Safety Data Sheet produced by the company for this product, which is available on request.

STORAGE

Tapes stored below the minimum recommended temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.





AFERA

Association des Fabricants Européens de Rubans Auto-Adhésifs.

Adding more to adhesive tape

Advance Tapes International Limited Westmoreland Avenue

Thurmaston
Leicester LE4 8PH

England

Tel. +44 (0)116 251 0191 Fax. +44 (0)116 265 2046 contact@advancetapes.com

