

DSFA215

Product	Double-Coated PE Foam Tape
Liner	White PE paper 110gsm
Carrier	Closed cell PE Foam, Density 64kg/m ³
Adhesive	High performance solvent acrylic, pressure sensitive
Description	This pressure sensitive mounting tape with solvent acrylic adhesive is suitable for interior as well as exterior applications and combines high initial tack with good cohesion and adhesion. Suitable for use on moderately uneven surfaces.
Range of application	Automotive accessory mounting, interior / exterior trims, towel hooks, exterior display mounting, sign assembly
Application temperature	18°C - 25°C

Total Thickness	1.5mm - 1.6mm			<p>Prior to application the surface should be made dry and free of any dirt, dust and grease. Use sufficient pressure over the whole surface at room temperature to ensure max. adhesive contact.</p>
Coating Thickness (Side A/B)	0.050mm - 0.060mm			
Temperature resistance	-20°C - 80°C			
Initial Tack (Side A/B) (PSTC-6 #14 ball)	< 5 cm			
Holding Power (Side A/B) (PSTC-7)	> 24 hrs 1 kg/2.5cmx2.5cm			
Holding Power for temperature resistance 60°C (PSTC-7)	> 24 hrs 0.5kg/2.5cmx2.5cm			
Adhesion (Side A/B) (PSTC-1)	g/2.5cm	OZ/in	N/2.5cm	
	>2000	>70.50	>19.5	
Solvent resistance	Good			

Figures shown refer to average values only, based on tests carried out in laboratory conditions and are not valid for specification. The company reserves the right to modify or change the product at any time without notice. All information has to be intended as generic advice for the use of products. Users have to verify the suitability of each tape in actual application under specific conditions.

Tel: +44 (0) 1213776070 Fax: + 44 (0) 121 3777175

www.genfab.co.uk Email: info@genfab.co.uk
 General Fabrications Ltd, Orphanage Road, Erdington, Birmingham, B24 9HT
 Registered in England No. 453031