

DSFA230

Product	Double-Coated PE Foam Tape, 3.0mm
Liner	White PE paper 110gsm
Carrier	Closed cell PE Foam, Density 48kg/m ³
Adhesive	High performance solvent acrylic, pressure sensitive
Description	This pressure sensitive mounting tape with solvent acrylic adhesive is suitable for interior as well as exterior applications and features good adhesion and holding power. Suitable for use on uneven surfaces. UV and weather resistant
Range of application	Sign assembly, nameplates, construction
Application temperature	18°C - 25°C

Total Thickness	3.0mm			Prior to application the surface should be made dry and free of any dirt, dust and grease. Use sufficient pressure over the whole surface at room temperature to ensure max. adhesive contact.
Coating Thickness (Side A/B)	0.050mm - 0.060mm			
Temperature resistance	-20°C - 80°C			
Initial Tack (Side A/B) (PSTC-6 #14 ball)	< 6 cm			
Holding Power (Side A/B) (PSTC-7)	> 24 hrs 1 kg/25mm x 25mm			
Holding Power for temperature resistance 60°C (PSTC-7)	> 24 hrs 0.5kg/25mm x 25mm			
Adhesion (Side A/B) (PSTC-1)	g/25mm >2500	OZ/in >88.2	N/25mm >24.4	
Solvent resistance	Good			
Test Method :ASTM				

Figures shown refer to average values only, based on tests carried out in laboratory conditions and are not valid for specification. The company reserves the right to modify or change the product at any time without notice. All information has to be intended as generic advice for the use of products. Users have to verify the suitability of each tape in actual application under specific conditions.

Tel: +44 (0) 1213776070 Fax: + 44 (0) 121 3777175

www.genfab.co.uk Email: info@genfab.co.uk

General Fabrications Ltd, Orphanage Road, Erdington, Birmingham, B24 9HT
Registered in England No. 453031