

Product Specification Last updated Sep-12

Page 1 of 1

DSFA501A

Product	Double-Coated PE Foam Tape		
Liner	White 0.08mm		
Carrier	Closed cell PE Foam, 48kg/m³		
Adhesive	High performance solvent acrylic, pressure sensitive		
Description	This pressure sensitive mounting tape with solvent acrylic adhesive is suitable for interior as well as exterior applications and combines high initial tack with good adhesion and moderate cohesion. Suitable for use on fairly uneven surfaces.		
Range of application	Interior / exterior trims		
Application temperature	18°C - 25°C		

Total Thickness	1.0mm - 1.1mm		
Coating Thickness (Side A/B)	e A/B) 0.040mm		
Temperature resistance	-20°C - 80°C		
Initial Tack (Side A/B)	< 5 cm		
(#14 ball, PSTC-6)			
Holding Power (Side A/B)	> 24 Hrs		
(PSTC-7)	1 kg/2.5cmx2.5cm		
Holding Power for temperature	> 24 Hrs		
resistance 60°C (PSTC-7)	0.5kg/2.5cmx2.5cm		
180° Peel Adhesion (Side A/B)	g/2.5cm	OZ/in	N/2.5cm
(SUS#304, PSTC-1)	>1500	>52.9	>14.6

Prior to application the surface should be made dry and free of any dirt, dust and grease. Use sufficient pressure over the whole surface at room temperature to ensure max. adhesive contact.

General Fabrications Ltd, Orphanage Road, Erdington, Birmingham West Midlands B24 9HT Tel: 0121 3776070 www.genfab.co.uk Email:info@genfab.co.uk

All statements, technical information and recommendations are based on tests we believe to be reliable, but the accuracy and completeness thereof is not guaranteed and the following is made in lieu off all warrantees, expressed or implied, including the implied warrantees of merchantability and fitness for purpose: Seller's and Manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, User shall determine the suitability of the product for its intended use, and User assumes all risk and liability whatsoever in connection therewith. Seller reserves the right to improve the product and accordingly change the specification without notice. Neither Seller nor Manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential, arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of or Seller and Manufacturer.