

<b>Product Overview</b>	<b>Low temperature application</b> with excellent initial tack and end strength at temperatures as low as 0°C. For High Medium surface energy substrates.
<b>Liner</b>	Red PE Film ( paper liner is available)
<b>Colour</b>	<b>Light Grey</b>
<b>Range of Applications</b>	Capable of absorbing the differing thermal expansion of two different materials. Maintains high impact resistance even at low temperatures. For many exterior applications, requiring high bond strength and resistance to UV and Solvents.

Test Characteristic	Units	Standard Values	Tolerance	Test Method
<b>Total Thickness (no liner)</b>	<b>mm</b>	<b>1.2</b>	<b>+/- 10%</b>	
<b>Temperature Resistance</b>		<b>100°C long term, 160°C Short term Min temperature -40°C</b>		
<b>90° Peel Adhesion to steel</b>	<b>N/cm</b>	<b>38</b>		<b>ASTM897</b>
<b>Static Shear</b>	<b>kpa</b>	<b>530</b>		<b>ASTM 3654</b>

Figures shown refer to average values only, based on tests carried out in laboratory conditions and are not valid for specification. The company reserves the right to modify or change the product at any time without notice.

All information has to be intended as generic advice for the use of products. Users have to verify the suitability of each tape in actual application under specific conditions

**Tel: +44 (0) 1213776070 Fax: + 44 (0) 121 3777175**

www.genfab.co.uk Email: info@genfab.co.uk

General Fabrications Ltd, Orphanage Road, Erdington, Birmingham, B24 9HT

Registered in England No. 453031