

Product	Double-Coated Tape
Liner	MOPP translucent red liner thickness 0.08mm.
Carrier	Transparent Mylar with thickness of 0.025mm
Adhesive	Cross linked solvent acrylic, pressure sensitive
Description	This tape has a strong Mylar base with a high tack solvent acrylic adhesive giving it excellent holding power and adhesion. Good resistance to weather conditions, UV, plasticizers and aging. The MOPP liner enhances transparency of the adhesive.
Range of application	Suitable for numerous fixing applications such as decorative and furniture trims, sign assembly, badge mounting, DIY and crafts.
Application temperature	18°C - 25°C; R.H. 55%±10%

Total Thickness	0.215mm - 0.225mm		
Coating Thickness (Side A/B)	0.095mm--0.100mm		
Temperature resistance	-20°C - 120°C		
Initial Tack (Side A/B) (PSTC-6 #14 ball)	< 5 cm		
Holding Power (Side A/B) (PSTC-7)	> 24 hrs 1 kg/2.5cmx2.5cm		
Holding Power for temperature resistance 60°C (PSTC-7)	> 24 hrs 0.5kg/2.5cmx2.5cm		
Adhesion (Side A/B) (PSTC-1)	g/25mm >2500	OZ/inch >88.19	N/25mm >24.4
Solvent resistance	Good		

Prior to application the surface should be made dry and free of any dirt, dust and grease. Use sufficient pressure over the whole surface at room temperature to ensure max. adhesive contact.

Test Method:ASTM

Figures shown refer to average values only, based on tests carried out in laboratory conditions and are not valid for specification. The company reserves the right to modify or change the product at any time without notice. All information has to be intended as generic advice for the use of products. Users have to verify the suitability of each tape in actual application under specific conditions

Tel: +44 (0) 1213776070 Fax: + 44 (0) 121 3777175

www.genfab.co.uk Email: info@genfab.co.uk

General Fabrications Ltd, Orphanage Road, Erdington, Birmingham, B24 9HT
Registered in England No. 453031