

<b>Product</b>	Low Tack Masking Tape up to 60 °C
<b>Backing</b>	Saturated Buff Crepe paper
<b>Adhesive</b>	Solvent Rubber Resin
<b>Range of Applications</b>	Specifically developed to mask pre-painted delicate surfaces
<b>Temperature resistance</b>	up to 60 °C

Test Characteristic	Units	Standard Values	Tolerance	Test Method
Total Weight (no liner)	g/m <sup>2</sup>	88	+/- 8%	ISO536
Total Thickness (no liner)	µm	115	+/- 10%	AFERA5006
MD Tensile Strength	N/cm	>28		AFERA5004
MD Elongation at Break	%	>8		AFERA5004
Adhesion to steel	N/cm	>1.3		AFERA5001

Figures shown refer to average values only, based on tests carried out in laboratory conditions and are not valid for specification. The company reserves the right to modify or change the product at any time without notice.

All information has to be intended as generic advice for the use of products. Users have to verify the suitability of each tape in actual application under specific conditions

**Tel: +44 (0) 1213776070 Fax: + 44 (0) 121 3777175**

www.genfab.co.uk Email: info@genfab.co.uk

General Fabrications Ltd, Orphanage Road, Erdington, Birmingham, B24 9HT  
Registered in England No. 453031