

Product datasheet Issue No 2

Issued April 2004

## **PPA 020 PERM/PEEL FILMIC ACRYLIC DOUBLE-SIDED TAPE, AMBER PAPER LINER**

<u>TECHNICAL DETAILS</u>	<u>TYPICAL VALUE</u>	<u>UNITS</u>
Thickness, adhesive + carrier	0.050	mm
Release liner thickness	0.075	mm
180 degree peel adhesion:      Open side	400	N/m
Closed side	150	N/m
Polyester loop tack:              Open side	800	N/m
Closed side	100	N/m
Liner release	10	N/m
Tensile strength	4600	N/m
Elongation at break	12	%
Service temperature	-20 TO +120	Deg. C.
Recommended application temperature	+5 TO +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.	>2	Hours
Shelf life	12	Months
Test Methods: BS 7116		

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.  
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR  
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.

**Tel: +44 (0) 1213776070 Fax: + 44 (0) 121 3777175**

[www.genfab.co.uk](http://www.genfab.co.uk) Email: [info@genfab.co.uk](mailto:info@genfab.co.uk)

General Fabrications Ltd, Orphanage Road, Erdington, Birmingham, B24 9HT  
Registered in England No. 453031