

<b>Product</b>	SMA 44 Double Sided Scrim
<b>Liner</b>	Polyolefin moisture resistant liner
<b>Description and Range of Applications</b>	Double sided scrim tape with high tack modified acrylic adhesive. Excellent ageing and weathering properties. Adheres to a wide range of substrates including low surface energy substrates ( e.g. Polypropylene, Polyethylene)

Test Characteristic	Units	Standard Values	Tolerance	Test Method
Total Weight (no liner)	g/m <sup>2</sup>	155	+/- 10%	ISO536
Total Thickness (no liner)	mm	0.15	+/- 10%	AFERA5006
Temperature Resistance	°C	-40 to +80		AFERA5004
Adhesive Strength	Min 24N/25mm	1 hour		AFERA5001

Figures shown refer to average values only, based on tests carried out in laboratory conditions and are not valid for specification. The company reserves the right to modify or change the product at any time without notice.

All information has to be intended as generic advice for the use of products. Users have to verify the suitability of each tape in actual application under specific conditions

**Tel: +44 (0) 1213776070 Fax: + 44 (0) 121 3777175**

www.genfab.co.uk Email: info@genfab.co.uk

General Fabrications Ltd, Orphanage Road, Erdington, Birmingham, B24 9HT

Registered in England No. 453031