

Description

700 micron amber coloured self wound double sided adhesive tape with internal scrim to give additional strength in use. The adhesive is coated onto a 100gsm white kraft siliconised differential release liner.

Application(s)

- Sign Fixings, Edgings and Trims
- Joining of sheets and Damp Proof Membranes
- Adhering Insulation to Walls
- Bonding GRP Roof Skins and Aluminium in the Commercial Bodybuilding Industry
- Fixing of Floor Materials such as Carpets and Strips
- Temporary Tarpaulin Repair

Technical Data

Thickness	:	700mu
Release Liner	:	Differential siliconised kraft liner paper 100g/m ²
Tensile Strength	:	88 N/25mm
Elongation at break	:	12%
Peel Strength	:	Open side (20 mins) 45 N/25mm : (FINAT FTM 1 – Stainless Steel) 1.8 kN/m : Open side (24 hrs) 65 N/25mm : (FINAT FTM 1 – Stainless Steel) 2.6 kN/m : Closed side (20 mins) 60 N/25mm : (FINAT FTM 1 – Stainless Steel) 2.4 kN/m : Closed side (24 hrs) 65 N/25mm : (FINAT FTM 1 – Stainless Steel) 2.6 kN/m
Initial Tack	:	(FINAT FTM 9 – Stainless Steel) 18 N/25mm 0.7 kN/m
Shear Strength (3kg static shear)	:	>800 hours
Service Temperature	:	5°C to 60°C
Shelf Life	:	2 years (+15°C to 25°C or +50°F to 77°F) And 50% relative humidity in dust free environment before use and in original packaging

Note: Where not indicated otherwise the above values are minimum expected values for each parameter measured.

The above information is given in good faith and for guidance only. The user shall be responsible for determining that the performance of the product is sufficient for his application. The quoted values are based on averages and should not be taken as maximum or minimum values for specific purposes.