

Product datasheet Issue No 7 Issued Dec 2012

TIR032 DOUBLE-SIDED TISSUE TAPE ECONOMY GRADE

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Adhesive type: Pressure-sensitive hotmelt rubber/resin		
Thickness, adhesive + carrier	0.080	mm
Release liner thickness	0.055	mm
180 degree peel adhesion:		
Open side	800	N/m
Closed side	800	N/m
Polyester loop tack:		
Open side	850	N/m
Closed side	850	N/m
Liner release	10	N/m
Tensile strength	1200	N/m
Elongation at break	10	%
Service temperature	-10 to +60	Deg. C.
Recommended application temperature	+5 to +60	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.	Greater than 100	Hours
Shelf life	12	Months
Test Methods: BS 7116		

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.

Tel: +44 (0) 1213776070 Fax: + 44 (0) 121 3777175

www.genfab.co.uk Email: info@genfab.co.uk

General Fabrications Ltd, Orphanage Road, Erdington, Birmingham, B24 9HT
Registered in England No. 453031