

Provisional Product datasheet Issue No 1 Issued November 2010

TRR027 High performance transfer tape (TOFFEE TAPE)

<u>TECHNICAL DETAILS</u>	<u>TYPICAL VALUE</u>	<u>UNITS</u>
Available Thicknesses	0.200 - 0.8mm	
Release liner thickness	0.080	mm
180 degree peel adhesion:		
Open side	>1000	N/m
Closed side	N/A	N/m
Polyester loop tack:		
Open side	>1000	N/m
Closed side	N/A	N/m
Liner release	10	N/m
Tensile strength	N/A	N/m
Elongation at break	4	%
Service temperature, continuous	-10 to +60	Deg. C.
UV Resistance	Moderate	
Recommended application temperature	+10 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.	>10	Hours
Shelf life	12	Months

Test Methods: BS 7116

*provides good bonding of LSE materials

The values quoted above are based on limited test data and may be subject to change

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.

Tel: +44 (0) 1213776070 Fax: + 44 (0) 121 3777175

www.genfab.co.uk Email: info@genfab.co.uk

General Fabrications Ltd, Orphanage Road, Erdington, Birmingham, B24 9HT
Registered in England No. 453031